

PRODUCT SPECIFICATIONS

REF#:FP-4001

3 Ft. Manual Shock Absorbing Rope Grab Assembly

DESIGN KEY FEATURES

- Equipped with energy absorber attached by a snap hook.
- 1.73" (44mm) wide tear webbing for energy absorption.
- 1.73" (44mm) wide polyester webbing as backup strap and stitched around the free end of tear webbing to form loops for attachment. The entire assembly folded and packed in thick Polyethylene sleeve with synthetic labels.
- Rope Grab is used for rope access.

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester

Width: 1.73" \pm 0.04" (44mm \pm 1mm)

Minimum Breaking strength: 6000 lbs (2722kg)

STITCHING THREAD:

Material: High-tenacity Polyester

WEIGHT:

2.60 lbs. \pm 0.02 lbs. (1179 gm. \pm 10 gm)

LENGTH:

3 Ft.



COMPLIANT WITH

Max Static strength	5000 lb
Max. Length	90cm
Max. Arrest Force	6 kN
EN User Capacity	100kg

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds ANSI Z359.1-2007

Scan here to visit website:

