

PRODUCT SPECIFICATIONS

REF#:FP-4003

Shock Absorbing Lanyard with Self-tracking Openable Rope Grab

DESIGN KEY FEATURES

- Self-tracking and openable Rope grab makes it convenient and more productive to work with
- High grade steel material makes it long lasting and highly durable
- Sets up in just seconds, as easy as unscrewing one screw and feeding the 5/8" vertical lifeline, then screwing it back together
- The rope grab is used over the twisted rope life line.
- Includes lanyard with integrated shock pack and snap hook to attach directly to back D-ring of harness
- Rope grab equipped with double locking closing mechanism

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester

STITCHING THREAD:

Material: High-tenacity Polyester

WEIGHT:

3.23 lbs. ± 0.02 lbs. (1465 gm. ± 10 gm)

LENGTH:

25 Ft.

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds ANSI Z359.1-2007



COMPLIANT WITH

Max Static strength	5000 lb
Max. Length	90cm
Life line length	3, 5, 10, 15, 20 meters
Max. Arrest Force	6 kN
EN User Capacity	100kg

Scan here to visit website:

