

# PRODUCT SPECIFICATIONS

**REF#:FP-5003**

Work Positioning Lanyard

## DESIGN KEY FEATURES

- Designed to hold the user in restraint, so a fall cannot occur, or to hold the user in a position of work where a fall may occur whilst allowing the user to work hands-free.
- Used by connecting the two ends of the Lanyard to the two Lateral D-rings on the work positioning belt of the harness of the user. The Length can be easily adjusted to suit the application.
- It is important to note that a Work Positioning System is not Fall Protection Equipment

## MATERIAL SPECIFICATIONS

### MATERIAL:

Kernmantle Rope

### ANCHORAGE ATTACHMENT:

Steel snap hook

### CONNECTING ATTACHMENT:

Grip Adjuster

### ROPE DIAMETER / WEBBING WIDTH:

12.0mm

### WEIGHT:

1.070kg

### LENGTH:

2.0m

## PERFORMANCE SPECIFICATIONS

### CERTIFICATION:

Meets or Exceeds EN354:2010, EN 358:2018



## COMPLIANT WITH

Static strength	5000 lb
Rope	5000 lb
Rope Adjuster	3600 lb
Connector	5000 lb
ANSI User Capacity	130 to 310 lb max
CE User Capacity	100 to 140 kg max

Scan here to visit website:

