

PRODUCT SPECIFICATIONS

REF#:FP-5005

Work Positioning Lanyard

DESIGN KEY FEATURES

- 1.57 in. (40mm) wide polyester tubular webbing incorporated with 1.18 in. (30mm) webbing
- Adjuster ring provides adjustment from 4-6 ft.
- Both ends of lanyard equipped with forged snap hook

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester

Width: 1.57 in. \pm 0.04 in. (40mm \pm 1mm)

Tensile Strength: 7000 lbs. (3175kg)

STITCHING THREAD:

Material: High-tenacity polyester

MATAL COMPONENT:

Material: Alloy steel


Plating: Zinc plated

Finish: Shot blasted

Breaking Strength: 23 kN (5000 lbs.) (2268kg)

WEIGHT:

2.29 lbs. \pm 0.02 lbs. (1040 gm \pm 10 gm)



PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN354:2010, EN358:2018, ANSI Z359.3-2017

COMPLIANT WITH

Static strength	5000 lb
Rope	5000 lb
Rope Adjuster	3600 lb
Connector	5000 lb
ANSI User Capacity	130 to 310 lb max
CE User Capacity	100 to 140 kg max

Scan here to visit website:

