

PRODUCT SPECIFICATIONS

REF#:FP-6002

Temporary Webbing Anchorage

DESIGN KEY FEATURES

- Made up of 1.73 in. (44mm) wide polyester webbing
- Stitched with 2.76 in. (70mm) webbing on the back for extra protection
- With a small D-ring at one end and a bigger D-ring at the other end

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester

Width: 1.73 in. \pm 0.03 in. (44mm \pm 1mm)

Breaking Strength: 5000 lbs. (Min.)

STITCHING THREAD:

Material: High-tenacity polyester

LENGTH:

3 ft.

WEIGHT:

0.57 lbs. \pm 0.02 lbs. (259 gm \pm 10 gm)

D-RING:

Material: Alloy steel

Breaking Strength: 5000 lbs. (Min.)

Finish: Golden Yellow Galvanized



COMPLIANT WITH

Static strength	5000 lb
Webbing	5000 lb
D-ring	5000 lb
Life line length	90cm, 120cm, 150cm, 180cm
EN User Capacity	100kg

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN795:2012 Type B, ANSI Z359.18-2017

Scan here to visit website:

