

# PRODUCT SPECIFICATIONS

**REF#:FP-7002**

Energy Absorber with Single Lanyard

## DESIGN KEY FEATURES

- Single leg lanyard incorporated with energy absorber
- One end equipped with steel snap hook and the other end equipped with rebar hook

## MATERIAL SPECIFICATIONS

### WEBBING:

Material: Polyester

Width: 1.18 in.  $\pm$  0.04 in. (30mm  $\pm$  1mm)

Breaking Strength: 6000 lbs. (2722kg)

### STITCHING THREAD:

Material: High-tenacity polyester

### MATAL COMPONENT:

Material: Alloy steel

Finish: Silver or Golden Yellow Galvanized

Breaking Strength: 5000 lbs. (2268kg)

### WEIGHT:

3.61 lbs.  $\pm$  0.02 lbs. (1640 gm  $\pm$  10 gm)



## PERFORMANCE SPECIFICATIONS

### CERTIFICATION:

Meets or Exceeds EN355:2002, ANSI Z359.13-2013

## COMPLIANT WITH

<b>Static strength</b>	5000 lb
<b>ANSI Lanyard Class</b>	6' Free fall
<b>Max. Arrest Distance</b>	48"
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1800 lb
<b>ANSI User Capacity</b>	130 to 310 lb max
<b>OSHA User Capacity</b>	130 to 310 lb max

Scan here to visit website:

