

**REF#:FP-7008**

Internal Energy Absorber with Single Lanyard

**DESIGN KEY FEATURES**

- 1.57 in. (40mm) wide polyester tubular elasticated webbing incorporated with energy absorbing (6 ft.) POY webbing
- One end equipped with steel stamped snap hook and the other end equipped with a steel rebar hook

**MATERIAL SPECIFICATIONS**

**WEBBING:**

Material: Polyester  
Width: 1.57 in. ± 0.04 in. (40mm ± 1mm)  
Breaking Strength: 5000 lbs. (2268kg)

**STITCHING THREAD:**

Material: High-tenacity polyester

**MATAL COMPONENT:**

Material: Alloy steel  
Plating: Zinc plated  
Finish: Shot blasted  
Breaking Strength: 5000 lbs. (2268kg)

**WEIGHT:**

6.06 lbs. ± 0.02 lbs. (2750 gm ± 10 gm)

**PERFORMANCE SPECIFICATIONS**

**CERTIFICATION:**

Meets or Exceeds EN355:2002, ANSI Z359.13-2013



**COMPLIANT WITH**

<b>Static strength</b>	5000 lb
<b>ANSI Lanyard Class</b>	6' Free fall
<b>Max. Arrest Distance</b>	48"
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1800 lb
<b>ANSI User Capacity</b>	130 to 310 lb max
<b>OSHA User Capacity</b>	130 to 310 lb max

Scan here to visit website:

