

REF#:FP-7010

Internal Energy Absorber with Double Lanyards

DESIGN KEY FEATURES

- Y shaped 1.57 in. (40mm) wide polyester tubular webbing incorporated with energy absorber (6 ft.)
- Polyester webbing with a steel stamped snap hook at one end and steel rebar hooks at the other two ends

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester
Width: 1.57 in. ± 0.04 in. (40mm ± 1mm)
Breaking Strength: 6000 lbs. (2722kg) - Min

STITCHING THREAD:

Material: High-tenacity polyester

MATAL COMPONENT:

Material: Alloy steel
Plating: Zinc plated
Finish: Shot blasted
Breaking Strength: 5000 lbs. (2268kg)

WEIGHT:

6.06 lbs. ± 0.02 lbs. (2750 gm ± 10 gm)

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN355:2002, ANSI Z359.13-2013



COMPLIANT WITH

Static strength	5000 lb
ANSI Lanyard Class	6' Free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1800 lb
ANSI User Capacity	130 to 310 lb max
OSHA User Capacity	130 to 310 lb max

Scan here to visit website:

