

**OSHA 1926.502(d)(21)**

Personal fall arrest systems shall be inspected before each use. In case of damage, deterioration and defective components, it should be removed from maintenance services.

**6.1 Inspection**

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year

Frequency of inspection in the following categories:

General Industry: _____ Construction: _____

Your Organization: _____ Manufacturer: _____

Manufacturer of equipment:

Name of Manufacturer: _____

Serial #: _____ Model #: _____

Date of Manufacture: ____ / ____ / ____

Inspection:

Date: ____ / ____ / ____

Name of competent person:

Name of user (authorized person):

**INSPECT 1 HARDWARE 2 CONNECTOR****3 STITCHING 4 LABELS/TAG**

1	HARDWARE	PASS	FAIL	NOTE
	Signs of Deformity			
	D-Ring / Connection Points			
	Hook Gate / Rivets (if applicable)			
	Corrosion / Pitting / Nick			

2	CONNECTOR	PASS	FAIL	NOTE
	Termination (Splice, or Swage)			
	Deterioration / Corrosion			
	Cuts / Burns / Hole			
	Integrity of Welds / Rivets			
	Paint Contamination			
	Heat Corrosion / UV Damage			
	Separation / Bird-Caging			
	Other			

3	STITCHING	PASS	FAIL	NOTE
	Missing			
	Loose			
	Broken			
	Other			

4	LABELS/TAGS	PASS	FAIL	NOTE
	Missing			
	Illegible			
	Dates			
	Other			

*Before inspection, please carefully review the operating instructions to fully understand the structure and compatibility of the equipment.

