

**OSHA 1926.502(d)(21)**

Personal fall arrest systems shall be inspected before each use. In case of damage, deterioration and defective components, it should be removed from maintenance services.

**6.1 Inspection**

6.1.1 Equipment SHALL be inspected by the user before each use and, additionally, by a competent person other than the user at intervals of no more than one year

Frequency of inspection in the following categories:

General Industry: _____ Construction: _____

Your Organization: _____ Manufacturer: _____

Manufacturer of equipment:

Name of Manufacturer: _____

Serial #: _____ Model #: _____

Date of Manufacture: ____ / ____ / ____

Inspection:

Date: ____ / ____ / ____

Name of competent person:

Name of user (authorized person):

**INSPECT 1 HARDWARE 2 WEBBING****3 STITCHING 4 LABELS/TAG**

1	HARDWARE	PASS	FAIL	NOTE
	Rust/corrosion			
	Deformed/bent			
	Burrs/cracks			
	Weld spots/slag			
	Missing rivets			
	Springs			
	Functionality			
	Other			

2	WEBBING/ROPE	PASS	FAIL	NOTE
	Cuts/burns/holes			
	Excessive wear			
	Excessive UV damage			
	Chemical attack			
	Other			

3	STITCHING	PASS	FAIL	NOTE
	Missing			
	Loose			
	Broken			
	Other			

4	LABELS/TAGS	PASS	FAIL	NOTE
	Missing			
	Illegible			
	Dates			
	Other			

*Before inspection, please carefully review the operating instructions to fully understand the structure and compatibility of the equipment.

