

PRODUCT SPECIFICATIONS



REF#:FP-5002

Work Positioning Lanyard

DESIGN KEY FEATURES

- Designed to hold the user in restraint, so a fall cannot occur, or to hold the user in a position of work where a fall may occur whilst allowing the user to work hands-free.
- Used by connecting the two ends of the Lanyard to the two Lateral D-rings on the work positioning belt of the harness of the user. The Length can be easily adjusted to suit the application.
- It is important to note that a Work Positioning System is not Fall Protection Equipment

MATERIAL SPECIFICATIONS

MATERIAL:

Kernmantle Rope

ANCHORAGE ATTACHMENT:

Steel snap hook

CONNECTING ATTACHMENT:

Aluminum Adjuster

ROPE DIAMETER / WEBBING WIDTH:

12.0mm

WEIGHT:

0.655kg

LENGTH:

1.8m

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN354:2010, EN 358:2018



COMPLIANT WITH

Static strength	5000 lb
Rope	5000 lb
Rope Adjuster	3600 lb
Connector	5000 lb
ANSI User Capacity	130 to 310 lb max
CE User Capacity	100 to 140 kg max

Scan here to visit website:



© copy right
all rights reserved

Poyan (Shanghai) Industry Co.Ltd

Building 1J, No. 2222 Huancheng Road, Jiading District, Shanghai
poyan@poyansafety.com

<https://poyansafety.com>