

PRODUCT SPECIFICATIONS



REF#:FP-7001

Energy Absorber with Single Lanyard

DESIGN KEY FEATURES

- Single leg lanyard incorporated with energy absorber
- Both ends equipped with steel snap hooks

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester
Width: 1.18 in. ± 0.04 in. (30mm ± 1mm)
Breaking Strength: 6000 lbs. (2722kg)

STITCHING THREAD:

Material: High-tenacity polyester

MATAL COMPONENT:

Material: Alloy steel
Finish: Silver or Golden Yellow Galvanized
Breaking Strength: 5000 lbs. (2268kg)

WEIGHT:

2.72 lbs. ± 0.02 lbs. (1234 gm ± 10 gm)



COMPLIANT WITH

Static strength	5000 lb
ANSI Lanyard Class	6' Free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1800 lb
ANSI User Capacity	130 to 310 lb max
OSHA User Capacity	130 to 310 lb max

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN355:2002, ANSI Z359.13-2013

Scan here to visit website:



© copy right
all rights reserved

Poyan (Shanghai) Industry Co.Ltd
Building 1J, No. 2222 Huancheng Road, Jiading District, Shanghai
poyan@poyansafety.com

<https://poyansafety.com>