

PRODUCT SPECIFICATIONS



REF#:FP-7006

Adjustable Energy Absorber with Double Lanyards

DESIGN KEY FEATURES

- Double, Y shaped webbing lanyard incorporated with energy absorber
- One end equipped with steel snap hook and the other end equipped with two steel rebar hooks
- Adjustable length by adjusters

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester

Width: 1.18 in. $\pm$ 0.04 in. (30mm $\pm$ 1mm)

Breaking Strength: 6000 lbs. (2722kg)

STITCHING THREAD:

Material: High-tenacity polyester

MATAL COMPONENT:

Material: Alloy steel

Finish: Silver or Golden Yellow Galvanized

Breaking Strength: 5000 lbs. (2268kg)

WEIGHT:

5.56 lbs. $\pm$ 0.02 lbs. (2520 gm $\pm$ 10 gm)

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN355:2002, ANSI Z359.13-2013



COMPLIANT WITH

Static strength	5000 lb
ANSI Lanyard Class	6' Free fall
Max. Arrest Distance	48"
Avg. Arrest Force	900 lb
Max. Arrest Force	1800 lb
ANSI User Capacity	130 to 310 lb max
OSHA User Capacity	130 to 310 lb max

Scan here to visit website:



© copy right
all rights reserved

Poyan (Shanghai) Industry Co.Ltd

Building 1J, No. 2222 Huancheng Road, Jiading District, Shanghai
poyan@poyansafety.com

<https://poyansafety.com>