

PRODUCT SPECIFICATIONS



REF#:FP-7015

Dielectric Energy Absorber with Single Lanyard

DESIGN KEY FEATURES

-Designed to be used in conditions where there are possible electrical hazards. Ideally used in Utilities, overhead Line teams on live wires protecting the user from Electrical discharge

MATERIAL SPECIFICATIONS

WEBBING:

Material: Polyester
Width: 1.18 in. ± 0.04 in. (30mm ± 1mm)

ANCHORAGE ATTACHMENT:

Dielectric Scaffold Hook

CONNECTING ATTACHMENT:

Dielectric Snap Hook

STITCHING THREAD:

Material: High-tenacity polyester

LENGTH:

1.8 m

WEIGHT:

1.39 kg



COMPLIANT WITH


Max Static strength	5000 lb
EN Lanyard Class	2 meters
Max. Arrest Distance	1.75 meters
Max. Arrest Force	6 kN
EN User Capacity	100kg

PERFORMANCE SPECIFICATIONS

CERTIFICATION:

Meets or Exceeds EN 355:2002

Scan here to visit website:



© copy right
all rights reserved

Poyan (Shanghai) Industry Co.Ltd
Building 1J, No. 2222 Huancheng Road, Jiading District, Shanghai
poyan@poyansafety.com

<https://poyansafety.com>