

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Room J5169, 3rd Floor, Building No. 2, No. 501 Pan'an Road, Jiading District, Shanghai, China

Declaration #

OQC25800010

Declaration Date

1/24/2025

Tested Item #

FP-8020

**Multi Dielectric FBH 80xx Construction Belted,
Medium, Mating Buckles**

Additional Items Conforming Under this Declaration:

FP-8020

FP-8021

FP-8022

FP-8023

Poyan Industry-declares that the product(s) listed above is in conformity with
the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

☐

Level 2

X

Level 3

☐

Level 1: Poyan Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: Poyan Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2501

Authorized Signature

Name

Title



Date



Test Report Number	PC-2501	Date	1/20/2025	Rev		Rev Date	
Report Prepared For	Poyan						
Initiated By	Zheng	Test Specification	ANSI Z359.13-2013 4.7.1, 4.7.2, 4.7.3, 4.8, 4.9, 4.13.1, 4.13.2, 4.13.3				
Base Part #	82608	Description	Full Body Harness				
Proposed Part #	N/A	Built By Whom	Production		BOM	No	
Test Request #	PC-2501	Date Received	1/15/2025	Date Complete		1/15/2025	
Test Operator	Kaen	Test Operator	Eson				

[illegible]

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3635.6 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage ≤ 1"	0.23"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3640.0 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage ≤ 1"	0.33"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3604.0 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage < 1"	0.31"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass





Poyan Test Report

Test Report No.	PC-2501	Rpt. Date	1/20/2025	Rpt. Rev		Rev Date	
Report Prepared For	Poyan						
Initiated By	Zheng	Test Specification(s)		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	8001			Part No. Revision		C	
Part Description	Multi Dielectric FBH-4 D-ring Industry / Construction Mating Buckles						
Test Request No.	PC-2501			Date Complete		1/24/2025	

Test Summary

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3665.6 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3650.7 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf $\geq$ 1 Minute	3660.1 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage < 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4552.3 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	3.7°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	11.6"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4406.7 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	3.3°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	10.3"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load > 3600 Lbf	4324.0 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest < 30°	2.9°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	9.8"	Pass



This laboratory is accredited in accordance with the recognized International Standard Module D This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system Poyan Testing Laboratory allows for a +/- 5% tolerance on dynamic and static strength test results.



@poyansafety.com
@poyansafety.com



Poyan Test Report

Test Report No.	PC-2501	Rpt. Date	1/20/2025	Rpt. Rev		Rev Date	
Report Prepared For	Poyan						
Initiated By	Zheng	Test Specification(s)		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	8127BM			Part No. Revision		C	
Part Description	Multi Dielectric FBH-4 D-ring Industry / Construction Mating Buckles						
Test Request No.	PC-2501			Date Complete		1/24/2025	

Test Summary Continued

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall	72" Free fall 3337.5 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	3.5°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall	72" Free fall 2082.7 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	5.1°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall	72" Free fall 2803.8 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest $\leq$ 30°	4.4°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

Conclusion

Based upon the samples provided to the Lab:
The samples meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval

Lab Quality Manager	zheng	Date	1/24/2025
Witnessed by	Kaen	Date	1/24/2025



This laboratory is accredited in accordance with the recognized International Standard Module D This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system Poyan Testing Laboratory allows for a +/- 5% tolerance on dynamic and static strength test results.



@poyansafety.com
@poyansafety.com